

MATERIAL SAFETY DATA SHEET

I. PRODUCT IDENTIFICATION

Name: Tandus Adhesive Systems
B-71 Tandus Broadloom Seam Sealer
Description: Vinyl acetate – ethylene copolymer emulsion

II. HAZARDOUS INGREDIENTS

None.
No toxic chemicals subject to the reporting requirements of Section 313 of Title III and of 40 CFR are present.
State Regulations: California Proposition 65
This product does not contain components listed under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65).

III. HMIS (0 = minimal hazard; 4 = severe hazard):

Health = 1 Flammability = 1 Reactivity = 0

IV. PHYSICAL PROPERTIES

Boiling Point: 212°F
Vapor Density (Air=1): Same as water.
Vapor Pressure: Same as water.
Percent Volatile by Volume: 28-30% (water)
Evaporation Rate (Water=1): Same as water
Appearance and Odor: Viscous latex emulsion, mild characteristic odor.
Specific Gravity: 1.04
Solubility in Water: Insoluble
VOC content: "0" grams/liter

V. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: > 212°F. METHOD USED: ASTM D-93. FLAMMABLE LIMITS IN AIR (% by Volume): Lower Non-flammable Upper Non-flammable. EXTINGUISHING MEDIA: Water, dry chemical, CO₂. AUTO-IGNITION TEMPERATURE: Not determined. UNUSUAL FIRE AND EXPLOSION HAZARDS: None known. Product is non-flammable in aqueous form. Dry product only will burn.

VI. HEALTH HAZARD DATA

CHRONIC OVEREXPOSURE: None known. THRESHOLD LIMIT VALUE: Not determined. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known. TOXICITY: No data available. ACUTE OVEREXPOSURE: EYE CONTACT: Avoid eye contact. Can cause mild to severe eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. INHALATION: Breathing of vapor may cause irritation of nose and throat. SKIN CONTACT: Avoid skin contact. Can cause skin irritation. Symptoms may include redness and burning of skin, or rash. SWALLOWING: Do not swallow. Swallowing may be harmful. Symptoms may include severe stomach and intestinal irritation (nausea, vomiting, diarrhea). LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN BY: NTP: No. I.A.R.C.: No. OSHA: No. EMERGENCY FIRST AID PROCEDURES: INHALATION: In case of overexposure move victim to fresh air. If breathing difficult, give oxygen. Get medical attention. EYE CONTACT: In case of eye contact flush eyes with water for at least 15 minutes. Seek medical attention if irritation persists. SKIN CONTACT: In case of contact wash skin with soap and water. INGESTION: If swallowed do not induce vomiting. Get medical attention immediately.

VII. REACTIVITY DATA/PHYSICAL HAZARDS

STABILITY: Stable.
CONDITIONS TO AVOID: None known.
INCOMPATIBLE MATERIALS: None known.
HAZARDOUS DECOMPOSITION PRODUCTS: None known.
HAZARDOUS POLYMERIZATION: Will not occur.



7/2006

B-71 SEAM SEALER for Broadloom Roll Goods

Tandus
P.O. Box 1447 · 1000 Vista Drive
Dalton, GA 30721
Emergency Telephone: 1 (800) 424-9300
Information Telephone: 1 (706) 259-9711
International Emergency:
Call USA 202-483-7616

VIII. SPECIAL PRECAUTIONS AND SPILL/LEAK PROTECTION

VENTILATION: General mechanical. RESPIRATORY PROTECTION: None required with adequate ventilation. GLOVES: Impervious. Neoprene rubber recommended. EYE PROTECTION: Safety glasses or splash proof goggles. OTHER: Keep containers closed and properly stored. Maintain an eyewash facility in the work area. TRANSPORTATION: D.O.T. Emergency Guide No.: Not regulated.

IX. PRECAUTIONS FOR SAFE HANDLING AND USE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store at 40°F - 110°F as recommendation. Provide adequate ventilation in the workplace. STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Cover small spills using inert absorbent, then sweep up and place in a waste disposal container. WASTE DISPOSAL METHODS: Dispose of in accordance with Federal RCRA and applicable State and Local regulations.

TANDUS BELIEVES THE DATA SET FORTH HEREIN ARE ACCURATE AS OF THE DATE HEREOF. TANDUS MAKES NO WARRANTY WITH RESPECT THERETO AND EXPRESSLY DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. SUCH DATA ARE OFFERED SOLELY FOR YOUR CONSIDERATION, INVESTIGATION AND VERIFICATION.