

MATERIAL SAFETY DATA SHEET

I. PRODUCT IDENTIFICATION

Name: C & A Floorcoverings
#99 Seam Sealer for Powerbond® Roll Goods
Description: Synthetic Polymer Mixture

II. HAZARDOUS INGREDIENTS

Chemical Names CAS # % ACGIH (TLV) OSHA (PEL)

None per OSHA Regulation: 29 CFR 1910.1200
The following chemicals are on the SARA Title III Section 313
Hazardous Chemical List: None
This product does NOT contain Asbestos.

III. HMIS (0 = minimal hazard; 4 = severe hazard):

Health = 1 Flammability = 0 Reactivity = 0

IV. PHYSICAL PROPERTIES

Vapor Density (Air=1): > 1
Boiling Point: 212°F
Specific Gravity: 1.03
Vapor Pressure: Same as water
Evaporation Rate: Same as water
Appearance & Odor: Cream Colored Liquid
Percent Volatile: 45-50% (by weight)
VOC content: ≤ 1 gram/liter

V. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A FLAMMABLE RANGE: N/A LEL: N/A UEL: N/A
EXTINGUISHING MEDIA: Water spray, foam, carbon dioxide, dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES: Protect fire fighters from toxic products of combustion by wearing self-contained breathing apparatus. UNUSUAL FIRE AND EXPLOSION HAZARDS: Not Known DOT CATEGORY: Not required.

VI. HEALTH HAZARD INFORMATION

SYMPTOMS OF OVEREXPOSURE: SKIN AND EYES: May produce slight transient irritation to the eyes or skin. INHALATION: May cause slight irritation of respiratory tract. INGESTION: Not a likely route of entry under proper handling conditions. May cause vomiting. Symptoms may be the same as inhalation. CARCINOGENICITY: No ingredient in this product has been identified as a carcinogen by NTP, IARC or OSHA. FIRST AID PROCEDURES: SKIN AND EYES: Flush any eye contact with plenty of water. With skin contact, wash with soap and water. Refer to physician if irritation develops or symptoms persist. INHALATION: Remove to fresh air, if needed. INGESTION: Seek medical attention if necessary.

VII. REACTIVITY DATA

STABILITY: Stable
CONDITIONS TO AVOID: Protect from freezing
INCOMPATIBILITY (Materials to avoid): Oxidizing Materials
HAZARDOUS DECOMPOSITION PRODUCTS: (including combustion Products): None known
HAZARDOUS POLYMERIZATION: Will not occur



#99 SEAM SEALER for Powerbond® Roll Goods

C & A Floorcoverings
P.O. Box 1447 · 1000 Vista Drive
Dalton, GA 30721
Emergency Telephone: 1 (800) 424-9300
Information Telephone: 1(706) 259-9711
International Emergency:
Call USA 202-483-7616

VIII. SPILL, LEAK & DISPOSAL PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED:

Use absorbent material to collect and contain for salvage or disposal. WASTE DISPOSAL: Abide by all state, federal and local regulation. Keep out of sewer and waterways.

IX. SPECIAL HANDLING INFORMATION

VENTILATION: Use local exhaust. RESPIRATORY PROTECTION: Should not be required. SKIN AND EYE PROTECTION: It is always a good safety practice to avoid contact with eyes and prolonged contact with skin. Use spectacle-type glasses and latex or rubber gloves to avoid contact. OTHER PROTECTIVE EQUIPMENT: None STORAGE: at 50-90°F and protect from freezing.

X. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Do not puncture. Shelf life is one year. KEEP OUT OF REACH OF CHILDREN.

C & A FLOORCOVERINGS BELIEVES THE DATA SET FORTH HEREIN ARE ACCURATE AS THE DATE HEREOF, C & A FLOORCOVERINGS MAKES NO WARRANTY WITH RESPECT THERETO AND EXPRESSLY DISCLAIMS ALL LIABILITY FOR RELIANCE THERON. SUCH DATA ARE OFFERED SOLELY FOR YOUR CONSIDERATION, INVESTIGATION AND VERIFICATION.

Revised 7/08