

MATERIAL SAFETY DATA SHEET

I. PRODUCT IDENTIFICATION

Name: C & A Floorcoverings
C-46E Premium Floor Primer
Description: Latex / Polymer Dispersion

II. HAZARDOUS INGREDIENTS

None

Chemical Names CAS # % ACGIH (TLV) OSHA (PEL)

None per OSHA Regulation: 29 CFR 1910.1200
The following chemicals are on the SARA Title III Section 313
Hazardous Chemical List: None. All components are on TSCA
inventory. *This product does NOT contain Asbestos.*

III. HMIS (0 = minimal hazard; 4 = severe hazard):

Health = 1 Flammability = 0 Reactivity = 0

IV. PHYSICAL PROPERTIES

Vapor Density (Air=1): > 1
Boiling Point: 212°F
Solubility in Water: Miscible **Specific Gravity:** 1.1
Vapor Pressure (mmHg at 20c): 250mPas **pH:** 5.0
Evaporation Rate (nBuAc=1): Same as water
Appearance & Odor: Cream Colored Liquid, sweet aromatic mild
Percent Volatile: Approx. 50% by weight(water)
VOC calculated: ≤ 1 grams/liter

V. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Pinsky-Martens C.C.: N/A Auto Ignition Temperature, F: N/A Flammability Limits in Air, Volume %: Lower N/A Upper: N/A **EXTINGUISHING MEDIA:** Water spray, foam, carbon dioxide, dry chemical. **SPECIAL FIRE FIGHTING PROCEDURES:** Wear self-contained breathing apparatus. **UNUSUAL FIRE AND EXPLOSION HAZARDS:** None
HAZARDOUS DECOMPOSITION PRODUCTS: combustion products): CO, CO₂, and NOX (including

VI. HEALTH HAZARD INFORMATION

SYMPTOMS OF OVEREXPOSURE: Inhalation: May cause slight irritation to upper respiratory tract. Eyes: May cause slight transient (temporary) eye irritation. Skin: May cause slight irritation. Ingestion: Not a likely route of entry under proper handling conditions. May cause vomiting. Symptoms may be the same as inhalation.
HEALTH EFFECT OR RISKS FROM EXPOSURE: **Acute:** May cause mild skin irritation, irritation of respiratory tract. **Chronic:** Prolonged eye contact to vapors or liquid may result in conjunctivitis; may cause mild skin irritation.
FIRST AID-EMERGENCY PROCEDURES: **Eye Contact:** Flush with water for at least 15 minutes. If irritation persists, seek medical attention, **Skin Contact:** Wash with soap and water. If irritation persists see a physician. **Inhalation:** Remove to fresh air, administer oxygen and if necessary, seek medical attention.
Ingestion: If swallowed, dilute with water and immediately induce vomiting. Never give fluids or induce vomiting if the victim is unconscious or having convulsions. Seek medical attention.
SUSPECTED CANCER AGENT: No **MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** None Known.

VII. REACTIVITY DATA

STABILITY: Stable
CONDITIONS TO AVOID: Protect from freezing
INCOMPATIBILITY(Materials to avoid): Oxidizing Materials
HAZARDOUS POLYMERIZATION: Will not occur
CORROSIVE TO METAL: No
OXIDIZER: No



C-46E PREMIUM FLOOR PRIMER

C & A Floorcoverings
P.O. Box 1447 · 1000 Vista Drive
Dalton, GA 30721
Emergency Telephone: 1 (800) 424-9300
Information Telephone: 1(706) 259-9711
International Emergency:
Call USA 202-483-7616

VIII. SPILL, LEAK & DISPOSAL PROCEDURES

Keep out of sewer systems to prevent blockage due to polymer deposits, soak up material with absorbent material (and sawdust) and place into closed containers for disposal. Note: Dispose of all wastes in accordance with Federal, State, Local regulations. **Environmentally Toxicity Data:** Fish Toxicity – LC50: 1500 mg/l (Goldfish, 96hr) **Hazardous Waste 40CFR261:** No **Hazardous Substance Superfund:** No

IX. SPECIAL HANDLING INFORMATION

VENTILATION: Use local exhaust. Do not used closed air circulation system. Open windows and doors if necessary. **RESPIRATORY PROTECTION:** Should not be required. Use product in a well-ventilated area. Use NIOSH approved respirator if irritation to respiratory tract. If vapors/mist are generated, wear NIOSH/MSHA approved organic vapor/mist respirator. **EYE PROTECTION:** Chemical goggles or face shield. **Protective Gloves:** Chemical resistant gloves **Other Clothing and Equipment:** If clothing becomes contaminated, remove and clean before re-wearing. **Work Practice, Hygienic Practices:** Follow all label instructions. **Other Handling and Storage Requirements:** Protect against physical damage. Store in cool dry place (50F-90F). Keep away from excessive heat. **Protective Measures During Maintenance of Contaminated Equipment:** Use goggles and gloves when cleaning adhesive from equipment. Maintain proper ventilation.

X. SHIPPING DATA

D.O.T. Proper ShippingName(49CFR172.101-102): None
Hazardous Substance (49CFR CERCLA List): No **RQ:** N/A
D.O.T. Hazardous Classification (49CFR 172.101-102)
Primary: None Secondary: None **D.O.T. Labels Required** (49CFR172,101-102): None
D.O.T. Placards Required (49CFR172.504) None **Poison Constituent** (49CFR172.203K): None
Bill of Lading Description (Plasticizer, resin or plastic).
CC NO.: 422 **UN/NA Code:** N/A

C & A FLOORCOVERINGS BELIEVES THE DATA SET FORTH HEREIN ARE ACCURATE AS THE DATE HEREOF, C & A FLOORCOVERINGS MAKES NO WARRANTY WITH RESPECT THERETO AND EXPRESSLY DISCLAIMS ALL LIABILITY FOR RELIANCE THERON. SUCH DATA ARE OFFERED SOLELY FOR YOUR CONSIDERATION, INVESTIGATION AND VERIFICATION.

Revised 7/08